

# CASTOR STEEL 150/20 CE

## STANDARD WORKING HEIGHT 10 M



**Steel ladder profil :** electrozinc-plated ladders, triangle beam offering an optimal resistance. Corrosion-resistant.

jusqu'à  
**20 m\***

**New working height :** up to 20 m\* maximum, vertically or at an angle.



Single phase 220 V - 50 Hz **electric winch** integrated into the ladder base. **0,75 kw power.**

max.  
**150 kg**



- **Haemmerlin technology at the best value for money.**
- The winch is integrated into the ladder base and thus protected against theft.
- Equipped with 120 L steel roofer platform with removable side panels for transportation of very bulky material. Optional front panel.
- Lifting speed : 20 m/min.
- Pre-angled steel knee joint adjustable from 20 to 60°.
- Ladder base equipped with a pair of wheels to facilitate handling.
- Can be installed inclined and vertically for a working angle of 30 to 90°.
- Non-detachable 220 V direct remote control.
- Universal trolley equipped with parachute system.
- Supports integrated in the knee joint and the headboard.
- Minimum generator power: 4.5 kVA.

DESIGNATION	PRODUCT CODE - EAN CODE
<b>CASTOR STEEL 150/20 - STRUCTURE 10 M</b>	311500701 3155031150075

**Bare structure** (no steel roofer platform) also available, to accessorise with compatible equipment of your choice, see below. **Not sold separately.**

*Our hoists do not include anchoring or shoring features, these accessories are optional.*