

# CONCRETE MIXER PRO TOWABLE


## PERFORMANCE 350

- Heated, towable concrete mixer.
- Large 290-litre mixing drum.
- Concrete mixer approved for a maximum speed of 90 km/h on the road (with ball hitch only). Drawbar with quick-release coupling system.
- Compact engine with low-oil safety cut-out. Steel pulley.
- Welded drum with reinforced rim. Drum locking via foot pedal and large-diameter handwheel. Handwheel with gear reduction to reduce the effort required for unloading.
- 3 high-strength, mechanically welded double blades: optimum mixing, high hourly output.
- Detachable drawbar and lighting bar.
- Mudguards as standard.
- Galvanised one-piece suspension axle. Lifting eye.
- Grease nipples on the drum bearings and on the pinion shaft.
- Adjustable belt tension.



2 bags of 35 kg  
Per mixing






Heavy-duty use. Major construction projects, concrete slabs, large-scale building sites.

### 350 l

Drum volume.

### 290 l

Mixing volume.



Honda GX 160 petrol engine. Power output: 4 kW, 5.5 hp. IP 44 protection.



- 1 Full protection for the steel rim: work in complete safety.
- 2 Large-diameter handwheel: less effort required. Force transmission and grease nipple on the handwheel shaft
- 3 Super-reinforced welded frame fitted with fork pockets.
- 4 Pedal for locking and unlocking the tank.
- 5 4 adjustable stabilisers.



Complete detachable lighting bar with a 7-pin caravan plug.

REFERENCE	DRUM EMPTYING	RIM	RIM PROTECTION	SOUND INTENSITY LEVEL (LWA)	ENGINE COVER	BELT	WHEELS	DIMENSIONS (L X L X H)	WEIGHT	PACKAGING & CODES
CONCRETE MIXER PERFORMANCE 350	Large-diameter steering wheel with power assistance	Cast iron	Steel sheet	97 dB	Steel sheet	Trapezoidal	Pneumatic wheels Ø 500 mm, on rims	1950 x 1230 x 1650 mm	249 kg	Assembled x1 Code 315540001 EAN 3155031554002

Technical manual supplied with the equipment. Also available to download from [www.haemmerlin.com](http://www.haemmerlin.com).