

# MAXIAL EXPERT 250/40 CE

STANDARD WORKING HEIGHT 10,5 M




Reinforced aluminium profil : strong and resistant, rustproof. Quick bolts - Easy Bolt.

up to  
**40 m\***

Working height : 20 m\* inclined and 40 m\* vertical.



Single phase 220 V - 50 Hz electric winch. Thermal protection. **1,5 kw power.**



- **The most powerful hoist on the market!** Reinforced ladders, 250 kg payload and up to 40 m\* of working height.
- Stable thanks to a wide structure and the **reinforced** ladders.
- Winch with **frequency converter** : soft start, reliability, motor and cable protection, low noise.
- Universal platform with expandable side and front panels for lifting bulky material, **capacity 273 L.**
- Extensions from 0.5 m, 1 m and 2 m for better height adjustment of the ladder structure.
- New generation double-ply adjustable knee joint from 0 to 60°.
- **High** lifting speed : 28 m/min.
- Easy installation and handling thanks to lightness of aluminium.
- Winch easily removable from ladder base and equipped with wheels for handling.
- Detachable 24 V remote control.
- Standard trolley equipped with parachute system.
- Bottom slack wire rope integrated into the winch, upper safety with hard stop.
- Bottom bumpers integrated into the ladder base.
- Minimum generator power : 6.5 kVA.

**The most POWERFUL**



DESIGNATION	PRODUCT CODE - EAN CODE
<b>MAXIAL EXPERT 250/40 - ROOFER 10,50 M</b>	312250401 3155031225049
ROOFER MODEL COMPOSITION	
Complete winch	1
Universal platform	1
Ø 6 mm L. 45 m cable (for max working height of 21 m)	1
2 m reinforced ladder base + quick bolts	1
2 m reinforced extension ladder + quick bolts	3
1 m reinforced extension ladder + quick bolts	1
Double-ply knee joint 0 to 60° + quick bolts	1
Headboard 1	1
Standard trolley	1
Detachable 24 V remote control (6 m cable)	1
Detachable 24 V top end switch with cable 20 m	1

*Our hoists do not include anchoring or shoring features, these accessories are optional.*

## COMPATIBLE ACCESSORIES

DESIGNATION	TECHNICAL FEATURES	PRODUCT CODE - EAN CODE
<b>REINFORCED EXTENSION LADDER 0,50 M</b>	Length 0,50 m. Reinforced profil. With 2 quick bolts.	312762101 - 3155031276218
<b>REINFORCED EXTENSION LADDER 1 M</b>	Length 1 m. Reinforced profil. With 2 quick bolts.	312762201 - 3155031276225
<b>REINFORCED EXTENSION LADDER 2 M</b>	Length 2 m. Reinforced profil. With 2 quick bolts.	312761901 - 3155031276195
<b>KNEE JOINT 0-60°</b>	Double-ply, adjustable from 0 to 60°. With 2 quick bolts.	312762501 - 3155031276256
<b>QUICK BOLT</b>	Sold individually.	312691701 - 3155031269173

