



# DM-200 WINCH - 24V CONTROL UNIT

## FIXED-ARM WINCH

**25 m**

Maximum working height of the hook.



Single-phase electric motor, 230 V / 50 Hz, 0.75 kW, IP55 rating.



max. 200 kg

COMES WITH A PAIR OF CLAMPS FOR USE ON Ø 49 MM TUBULAR SCAFFOLDING.



- Versatile lifting winch for renovation and construction sites.
- **Sturdy, lightweight, easy to handle, and simple to operate.**
- **Comes with a pair of scaffold clamps.**
- Fixed boom that pivots relative to the scaffold clamps or floor column.
- Detachable and extendable 24V low-voltage remote control: can be stored away to prevent theft and unauthorized use of the winch outside of working hours.
- Thanks to its compact size and light weight, the winch is quick and easy to set up.
- The winch requires very little maintenance.
- Lifting speed: 25 m/min.
- Lifting cable: 5 mm diameter, 25 m long.
- Maximum working height of the hook: 25 m.
- Safety feature: limit switch built into the winch.
- Weight: 37 kg.

DESIGNATION	PRODUCT CODE EAN CODE
<b>DM-200 JIB WINCH - 24V DC + PAIR OF SCAFFOLDING CLAMPS</b>	319371501 3155031937157

## ACCESSORIES

FOR DM-200 FIXED-BOOM WINCHES

DESIGNATION	TECHNICAL SPECIFICATIONS	PRODUCT CODE EAN CODE
<b>PAIR OF SCAFFOLDING COLLARS</b>	Clamp for use on scaffolding with Ø 49 mm tubes (325 mm center-to-center spacing).	319371701 - 3155031937171
<b>LIFTING CABLE Ø5 - 27 M</b>	Maximum height under hook: 25 m*.	319371901 - 3155031937195
<b>GALVANIZED CABLE SLING</b>	For mortar buckets. Maximum working load: 560 kg. Cable Ø 6 mm.	317001401 - 3155031700140
<b>90 L MORTAR TRAY</b>	Polypropylene - Ø 576 mm - H 385 mm. Load capacity 250 kg.	317903801 - 3155031790387
<b>200 L MORTAR TRAY</b>	Polypropylene - 910 x 585 x 490 mm. Load capacity 500 kg.	317001601 - 3155031700164

\* Cable must be crimped by a professional.

