



## AKTIV EXCELLIUM 100 GALVANIZED TRAY PNEUMATIC WHEEL

### Use

Designed for building and heavy duties.  
Loading capacity 200 kg.



### Product advantages

- **Patented frame CP2i®**, one-piece rigid frame, for strength and performance. 2/3 of the load is borne by the wheel and the length of the frame reduces stress during use. Its design allows optimal use and reduces risk of injury and strains for the user. Bi-material handgrips for added comfort.
- Best for building, renovation and do-it-yourself works, thanks to its galvanized anti-corrosion tray.
- Front and side ribbing for additional strength.
- Pneumatic wheel with ball bearings to enhance comfort.

### Technical data

#### AKTIV EXCELLIUM 100 GALVANIZED TRAY PNEUMATIC WHEEL (102 KG)

<b>Tray</b>	Galvanized 100 l, 1 mm thickness, treated anti-corrosion. Frontal and lateral ribs for additional strength.	<b>Sizes</b>	1420 x 680 x 610 mm.
<b>Frame</b>	CP2i® Ø 32 mm black painted with integrated tipping bar and tray supports.	<b>Weight</b>	12,2 kg.
<b>Wheel</b>	Pneumatic Ø 400 mm, with ball bearings, metal disc rim chrome-looking, long lasting notched tyre. Maximum pressure : 2 bars.	<b>Spare parts</b>	<b>Wheel PF 128</b> Code : 309032801 EAN : 315503090328 3 <b>Galvanized tray 100 l.</b> Code : 309007101 EAN : 315503090071 8
		<b>Packaging and codes</b>	Assembled x 5 : 305349605 EAN : 315503053497 5 Strapped x 14 : 304211611 EAN : 315503042116 9

