

PERFORMANCE CONCRETE MIXER CE

PERFORMANCE 350



Intensive use.
Major construction work, tiles, construction sites.

350 L

Drum volume

290 L

Mixing volume



Petrol Honda GX 160 motor. 3 kw power, 4 ch. Protection IP 44.



Drum transport position.



2 bags of 35 kg Per mixing



- **Thermic and towable** concrete mixer.
- **Extra large mixing tanks** from 290 L.
- Concrete mixer approved for a maximum speed of 90 km/hour (only with the fastener for towing ball). Tiller with **quick attaching system**.
- Compact motor with **lack of oil security**. Steel pulley.
- **Welded tank with reinforced side**. Tank blocking thanks to the pedal and steering wheel **high diameter with tilting movement ratio** to reduce the spilling effort.
- **Welded mechanical mixing blade** are **3 doubles** and **high resistance** for an optimum mixing and a high work yield.
- Removable tiller and **light bar. Standard mudguard**.
- Galvanised monobloc suspension axle. Lifting eye.
- Lubricators on drum bearings and pinion axle.
- Possibility to adjust the belt tension.



- 1 **Complete protection** of the rim : **reduces the risk of accidents**.
- 2 Steering wheel high diameter with tilting movement ratio : less effort to provide.
- 3 Welded mechanical frame reinforced and fitted with forks grips.
- 4 Locking and unlocking pedal of the tank.
- 5 4 **adjustable stabilizers**.

Detachable tow-bar.

DESIGNATION	DRUM SPILLING	RIM	RIM PROTECTION	SOUND INTENSITY LEVEL	ENGINE COVER	SERPENTINE BELT	WHEELS	DIMENSIONS (L X L X H)	WEIGHT	PRODUCT CODE EAN CODE
CONCRETE PERFORMANCE 350	Steering wheel high diameter with tilting movement ratio	Cast iron	Steel sheet	97 dB	Steel sheet	Trapezoid	Pneumatic Ø 250 mm on metal rim	1950 x 1230 x 1650 mm	249 kg	315540001 3155031554002



P.O. Box 30045 - 67701 SAVERNE Cedex - FRANCE
Tél. + 33 (0)3 88 01 85 13 - Fax + 33 (0)3 88 01 85 09
welcome@haemmerlin.com - www.haemmerlin.com