

MAXIAL EXCELLIUM 200/30 ^{CE}

STANDARD WORKING HEIGHT 10,5 M



Aluminium profil : solid and resistant ladders, do not rust. Quick bolts - **Easy Bolt**.

up to
30 m*

Working height : 20 m* inclined and 30 m* vertical



Single phase 220 V - 50 Hz **electric winch**. Thermal protection. **1,5 kw power**.



- **Large ladder support width**: better stability.
- Winch with **frequency converter** : soft start, reliability, motor and cable protection, low noise.
- Roofer platform with removable side panels, 197 L capacity, dimensions 558 x 445 x 794 mm. Optional front panel.
- **High lifting speed** : 28 m/min.
- Easy installation and handling thanks to lightness of aluminium.
- Winch easily removable from ladder base and equipped with wheels for handling.
- Pre-angled aluminium knee joints from 30 to 60°.
- Detachable 24 V remote control.
- Standard trolley equipped with parachute system.
- Bottom slack wire rope integrated into the winch, upper safety with hard stop.
- Bottom bumpers integrated into the ladder base.
- Minimum generator power : 6.5 kVA.

DESIGNATION	PRODUCT CODE - EAN CODE
MAXIAL EXCELLIUM 200/30 - STRUCTURE 10,50 M	312200001 3155031220006
Bare structure (no roofer platform) also available, to accessorise with compatible equipment of your choice. Not sold separately.	

Our hoists do not include anchoring or shoring features, these accessories are optional.