

MAXIAL PREMIUM 175/20

STANDARD WORKING HEIGHT 10,5 M



Aluminium profil : solid and resistant ladders, do not rust. Quick bolts - **Easy Bolt**.

up to
20 m*

Working height : up to 20 m* maximum, inclined and vertical.



Single phase 220 V - 50 Hz **electric winch**. Thermal protection. **1,1 kw power**.



- **Large ladder support width** : better stability.
- **New pre-angled knee joint** adjustable from 30 to 60°.
- Roofer platform with with removable side panels, 197 L capacity, dimensions 558 x 445 x 794 mm. Optional front panel.
- Easy installation and handling thanks to lightness of aluminium.
- Winch easily removable from ladder base and equipped with wheels for handling.
- Lifting speed : 22 m/min.
- Pre-angled aluminium knee joints from 30 to 60°.
- Detachable 24 V remote control.
- Standard trolley equipped with parachute system.
- Bottom slack wire rope integrated into the winch, upper safety with hard stop.
- Bottom bumpers integrated into the ladder base.
- Minimum generator power : 5,5 kVA.

DESIGNATION	PRODUCT CODE - EAN CODE
MAXIAL PREMIUM 175/20 - STRUCTURE 10,50 M	312175001 3155031217501
Bare structure (no roofer platform) also available, to accessorise with compatible equipment of your choice. Not sold separately.	

Our hoists do not include anchoring or shoring features, these accessories are optional.