

AKTIV EXCELLIUM PLUS 100

PAINTED PNEUMATIC WHEEL



Painted tray, with front and side ribbing for additional strength.



Alpha Frame with welded support which forms a strong cradle both at the front and on the underside of the tray to increase rigidity.



Bi-material handgrips = comfort and ergonomics when being used.



Stamped tray with «Made in France» marking.



USE

Designed for building, renovation and heavy duties.

TECHNICAL DATA

FRAME	VOLUME	CRASH-TEST	HANDGRIPS	WHEEL	WEIGHT
Alpha frame with integrated tipping bar and welded all round tubular support	Yellow painted 100 L tray 1,2 mm thickness	520 kg	Bi-material	Pneumatic Ø 400 mm, with ball bearings, metal disc rim, PF 128	14,1 kg

SIZES OF THE PRODUCT	PACKAGING	SIZES OF THE PALLET	PRODUCT CODE EAN CODE	SPARE PARTS
1420 x 680 x 610 mm	Assembled x 5	1585 x 800 x 2000 mm	305264106 3155030526390	Wheel PF 128 Code : 309032801 EAN : 3155030903283 Painted tray 100 L Code : 309008901 EAN : 3155030900893

CRASH-TEST

Static resistance test of the structural elements. Should not be confused with the maximal recommended load. Dangerous test. Need to be tested in a safe environment. Should not be reproduced.

CDH - H 03.21
Our products are susceptible to changes during the year. Photographs are non-contractual.



TESTS CONDUCTED BY THE LNE*

THE GUARANTEES OF HAEMMERLIN STANDARDS*



DYNAMIC LOAD



MOVING VOLUME

Usage : intensive
Resists over 12 000 obstacles crossings and spills, loaded with 120 kg, means:

1400 T carried

3,2 T carried per day,
220 days per year, for 2 years.

LOADS



125 KG
5 bags of 25 kg cement



100 KG
7 concrete blocks



120 KG
of sand or gravel

* National Metrology and Testing Laboratory