



AKTIV PREMIUM GALVA PNEUMATIC WHEEL



Galvanized tray, with front and side ribbing for additional strength.



Patented frame CP2i® : ergonomic and extremely stable, with integrated tipping bar and tray supports.



Ergonomic handgrips for a better grip and a better use comfort.



Stamped tray with «Made in France» marking.



USE

Designed for building and heavy duties.

TECHNICAL DATA

FRAME	VOLUME	CRASH-TEST	HANDGRIPS	WHEEL	WEIGHT
Black CP2i® with all round tubular support	Galvanized 100 L tray 0,9 mm thickness Treated anti-corrosion	380 kg	Ergonomic	Pneumatic Ø 380 mm, metal disc rim, PF 150	11,1 kg

SIZES OF THE PRODUCT	PACKAGING	SIZES OF THE PALLET	PRODUCT CODE EAN CODE	SPARE PARTS
1420 x 680 x 590 mm	Assembled x 24	1340 x 2400 x 2500 mm	305071724 3155030507177	Wheel PF 150 Code : 309051401 EAN : 3155030905140 Galvanized tray 100 L Code : 309009801 EAN : 3155030900985
	Assembled x 5	1585 x 800 x 2000 mm	305071705 3155030507177	



CRASH-TEST

Static resistance test of the structural elements. Should not be confused with the maximal recommended load. Dangerous test. Need to be tested in a safe environment. Should not be reproduced.

CDH - H 03.21
Our products are susceptible to changes during the year. Photographs are non-contractual.



TESTS CONDUCTED BY THE LNE*

THE GUARANTEES OF HAEMMERLIN STANDARDS*



DYNAMIC LOAD



MOVING VOLUME

Usage : regular
Resists over 7 500 obstacles crossings and spills, loaded with 100 kg, means:

750T carried

1,7T carried per day,
220 days per year, for 2 years.

LOADS



105 KG
3 bags of 35 kg cement



100 KG
6 concrete blocks



100 KG
of sand or gravel

* National Metrology and Testing Laboratory